


COMPANY PROFILE





novative, user-friendly, and solution-oriented systems. The past of the company lies into the manufacturing of classical compensation system and has earned a reputable name into the field of clean feed-in of modern renewable energy such as wind, solar and water energy. But the industrial users rely particularly on specialists from Sauerland when the topic of grid quality comes into the picture.

Do you have a power supply problem? Your machine doesn't work as desired? Your network suffers from voltage dips? Something is strange in your network?

We have the solution to get over that problem. Promised!

Providing a profound consultation and technical expertise based on high ecological and economical standards is our core competence and passion. In this brochure, we give you a quick overview of our product portfolio.

Dr. rer. nat. Christian Dresel



ive Power Compensation System First High Voltage Filter System 1973

Lepper Doiminit, later ASEA-Lepper, from 1982 ASEA Kondensatoren

Product launch: First controlled Low-Voltage Filter System

NETWORK PHENOMENA AND ITS CONSEQUENCES – CORRECT SOLUTION – FITTING PRODUCT

FLICKER, VOLTAGE SAGS AND SWELLS, AND VOLTAGE UNBALANCE

Flicker, voltage sags and swells and voltage unbalances are changes in the effective value of voltage. This effects can lead to production outages which are costly and unplanned. If the voltage drops below 85% of the nominal voltage, it could lead to the tripping of contactors, frequency converters and switching power supplies. With our GridClass® products THYRA and OSKAR®, we take care of such problems irrespective of the source.

HARMONIC VOLTAGE DISTORTIONS

With an increasing number of non-linear loads such as Switched Mode Power Supplies (SMPS), rectifiers, Variable Frequency Drives (VFD), which bear a non-linear characteristic, resulting into non-sinusoidal current consumption. This results into the generation of harmonics voltages whose frequency are the integer multiples of the network frequency, which in turn determines the order of that respective harmonic. Any device or equipment, whether mechanical or electrical, can only be loaded completely under defined conditions. Furthermore, industrial networks are subject to relevant standards which must be complied with. In case of networks not conforming these standards, the warranty claims are voided, since the equipment manufacturers are not obliged if there is no standard power supply. But from the customer's point of view, it is a functional defect of that device or equipment. With our GridClass® products SOFIA®, MIA® and MIKA, the "harmonics" are filtered and customer's power supply network is optimized and stabilized.

RESONANCE VOLTAGE DISTORTIONS

In addition to the harmonic voltage distortions, whose frequencies are the integer multiples of fundamental frequency, there are some more reasons for the distortion of the voltage waveforms. Self-commutated power converters of all types supply high-frequency voltage distortions based on the switching frequency of power electronics to the connected power supply. Thyristor controllers can produce commutation nodges of different depths up to double zero crossings. Network resonances caused by the interaction of capacitive and inductive components produce in some cases serious and destructive overvoltages. In virtually all cases where a resonance point exists, the resonance is either permanently excited by nonlinear loads or activated by switching processes.

ABB Capacitors

1988

Product launch: COMFIL Combi-Filter Systems, DYNACOMP Dynamic Compens. Active Harmonic Filter PQF, SCOMP encapsulated HS-System with arc fault test Market Innovation: ALFC Flicker compensation

In both cases, the non-harmonic voltage distortions can be attenuated using our products RESI, SOFIA®-HP and MIKA, so that disturbances of higher order voltage distortions do not burden the respective network.

REACTIVE POWER

Electrical loads, such as motors, transformers, welding machines, operate according to the induction principle and require inductive reactive power for the formation of the magnetic fields. This power is not converted into mechanical movement or heat, like the real power, but alternately oscillates between generator and load. The customer who requires this kind of power is charged based per kvar by the utility company. However, there are some relaxations. The most common specification for industrial customers is to maintain their power factor abuve $\cos \phi \approx 0.9$. The reference to the inductive reactive power is calculated with a working rate of, for example, 1 Cent/kvarh (Price sheet 10 of Westnetz). Thus, in addition to the active energy (real energy), the overconsumption of reactive energy (usage in kvarh) is calculated. These additional costs can be avoided by means of a reactive current compensation system by providing the inductive reactive current over-covering with choked capacitors and automatically regulated in power stages. Condensator Dominit is the compensation specialist and has the necessary tool for every type of reactive power. The harmonic filters SOFIA® and MIA® are used to compensate for distortion-free power. The capacitive systems THYRA and KLARA, the inductive INKA and the extensive CLASSIC range are available for fundamental oscillating reactive power. At last, the medium voltage compensation units of the MIKA group complete the unique product portfolio.

FREQUENCY DISTORTION

In European Network of Transmission System Operators for Electricity (UCTE), as well as in many other strong power distribution networks worldwide, the network frequency is subject to a very narrow tolerance range which is by default never violated. This tolerance range in Germany is in the range of 47.5 Hz to 51.5 Hz, thus guaranteeing a reliable guide for every consumer and every producer. Therefore, only the energy supplier is responsible for ensuring the grid frequency in the public distribution grid. The situation is different in the case of self-sustaining "island networks", as described, for example, in emergency power operation in hospitals or on ships. If the current-generating generator is too weak for the loads or if the generator feeds unwanted harmonic oscillations into the island network, the network is destabilized in this phenomenon as well. If there is a problem, then contact our team of experts in matters of grid quality. The Condensator Dominit team will be very glad to help you.

ation, ing. ABB Switchgears

Market Innovation: Broadband Filters (UBF)



LISA - DELIVERY, COMMISSIONING, SERVICE, ANALYSIS

Our service to our customer is the most important aspect of our business. We believe that the best product quality deserves the best support. For this reason, we offer you, through our LISA program, a tailored package for all your needs:

Analysis of your electrical network

We perform qualified studies of power supply networks (low and high voltage). In doing so, we are investigating the network not only to the range prescribed by standard (EN 50 160 etc.) up to 2,500 Hz but also beyond 20 kHz. It shows that more and more disturbances in frequency ranges > 2 kHz are available!

Upon completion of the measurement, the customer receives a report from us which contains:

- All measured values with diagram or table
- Summary of results
- Recommendation for required solution

Condensator Dominit

2005

Dr. Christian Dresel overtakes as the chairman of the company

2008

Market Innovati CLMQ II - Dynan special design fo



on:

nic compensation, r switching delays of 20 ms 2009

Market innovation:

AVS for voltage stabilization

FLICKER VOLTAGE DIPS VOLTAGE CONDITIONING OVERVOLTAGE UNBALANCE **FILTERING HARMONICS HARMONICS** HARMONICS OF DAMPENING OF HIGHER ORDER RESONANT **HARMONICS** RESONANCES COMPENSATING OF REACTIVE POWER REACTIVE **POWER**

INTERNAL REASONS

THYRA

EXTERNAL REASONS

OSKAR®

SOFIA®

MIKA

RESI SΦFIA®-HP MIKA

INDUCTIVE

INKA

THYRAKLARA **ZLASSIC**


MIKA


















Condensator Dominit GmbH An der Bremecke 8

D-59929 Brilon

Fon +49 (0) 2961 - 782-0 Fax +49 (0) 2961 782-36 E-Mail info@dominit.eu

Web www.condensator-dominit.de

Subject to changes. Errors and omissions excepted.